

# BF15

## Engine

Type	4-Stroke OHC Twin Cylinder
Displacement (cc)	350 cc (21.5 cubic in)
Bore and Stroke (mm)	59 x 64 mm (2.3 x 2.5 in)
Full throttle RPM range (rpm)	4,500 – 5,500 RPM
HP rating at Propshaft (HP)	15HP @ 5,000 RPM
Induction Scavenging	SOHC
Valves per cylinder	2
Fuel delivery	Single Venturi
Ignition system	Programmed Ignition system
Starting system	Manual/Electric
Lubrication	Wet Sump
Cooling system	Water Cooled
Alternator (Electric)	12 amp (148 watt)
Alternator (Manual)	6A (76W)
Trim Range (degrees)	4 Stage: 8°, 12°, 16°, 20°
Tilt Range (degrees)	72°

## Drive

Gear Ratio	2.08:1
Gear Shift	F-N-R
Propeller	4 Blade Aluminum (10 x 6 ½)

## Dimensions & Weight

Recommended transom height (S) (mm)	381 (15")
Recommended transom height (L) (mm)	508 (20")
Recommended transom height (X) (mm)	N/A
Recommended transom height (XX) (mm)	N/A
Dry Weight (S) (kg)	N/A
Dry Weight (L) (kg)	N/A
Dry Weight (X) (kg)	N/A
Dry Weight (XX) (kg)	N/A
Dry Weight Tiller (Manual) (S) (kg)	46 kg / 103 lbs
Dry Weight Tiller (Electric) (S) (kg)	50 kg / 110 lbs

Dry Weight Tiller (Manual) (L) (kg)	49 kg / 108 lbs
Dry Weight Tiller (Electric) (L) (kg)	53 kg / 117 lbs
Dry Weight Tiller (PTT) (L) (kg)	N/A
Dry Weight RC (S) (kg)	47/49 (103/109lbs)
Dry Weight RC (L) (kg)	47/49 (103/109lbs)
Dry Weight RC (X) (kg)	N/A
Dry Weight Power Tilt (S) (kg)	58 kg / 129 lbs
Dry Weight Power Tilt (L) (kg)	60 kg / 133 lbs