

BF2

Engine

Type	4-Stroke OHV Single Cylinder
Displacement (cc)	57 (3.4 cubic ")
Bore and Stroke (mm)	45 x 36 (1.8 x 1.4")
Full throttle RPM range (rpm)	5000-6000
HP rating at Propshaft (HP)	2@5500RPM
Induction Scavenging	OHV
Valves per cylinder	2
Fuel delivery	Single Venturi
Ignition system	Transistor Pointless
Starting system	Manual
Lubrication	Wet Sump
Cooling system	Forced Air
Alternator (Electric)	N/A
Alternator (Manual)	N/A
Trim Range (degrees)	4-Stage 5°-10°-15°-20°
Tilt Range (degrees)	75°

Drive

Gear Ratio	2.11:1
Gear Shift	N/A
Propeller	3 Blade Polypropylene

Dimensions & Weight

Recommended transom height (S) (mm)	381 (15")
Recommended transom height (L) (mm)	508 (20")
Recommended transom height (X) (mm)	N/A
Recommended transom height (XX) (mm)	N/A
Dry Weight (S) (kg)	12 (27lbs)
Dry Weight (L) (kg)	12.7 (28lbs)
Dry Weight (X) (kg)	N/A
Dry Weight (XX) (kg)	N/A
Dry Weight Tiller (Manual) (S) (kg)	N/A
Dry Weight Tiller (Electric) (S) (kg)	N/A

Dry Weight Tiller (Manual) (L) (kg)	N/A
Dry Weight Tiller (Electric) (L) (kg)	N/A
Dry Weight Tiller (PTT) (L) (kg)	N/A
Dry Weight RC (S) (kg)	N/A
Dry Weight RC (L) (kg)	N/A
Dry Weight RC (X) (kg)	N/A
Dry Weight Power Tilt (S) (kg)	N/A
Dry Weight Power Tilt (L) (kg)	N/A