

# BF20

## Engine

Type	4-Stroke OHC Twin Cylinder
Displacement (cc)	350 (21.4 cubic ")
Bore and Stroke (mm)	59 x 64 (2.30 x 2.51")
Full throttle RPM range (rpm)	5000-6000
HP rating at Propshaft (HP)	20@5500RPM
Induction Scavenging	SOHC
Valves per cylinder	2
Fuel delivery	Single Venturi
Ignition system	Programmed Ignition System
Starting system	Manual/Electric
Lubrication	Wet Sump
Cooling system	Water Cooled
Alternator (Electric)	12A (148W)
Alternator (Manual)	6A (76W)
Trim Range (degrees)	4 Stage 8°-12°-16°-20°
Tilt Range (degrees)	72°

## Drive

Gear Ratio	2.08:1 (13/27)
Gear Shift	F-N-R
Propeller	4 Blade Aluminum

## Dimensions & Weight

Recommended transom height (S) (mm)	381 (15")
Recommended transom height (L) (mm)	508 (20")
Recommended transom height (X) (mm)	N/A
Recommended transom height (XX) (mm)	N/A
Dry Weight (S) (kg)	N/A
Dry Weight (L) (kg)	N/A
Dry Weight (X) (kg)	N/A
Dry Weight (XX) (kg)	N/A
Dry Weight Tiller (Manual) (S) (kg)	46 (103lbs)
Dry Weight Tiller (Electric) (S) (kg)	50 (110lbs)

Dry Weight Tiller (Manual) (L) (kg)	49 (108lbs)
Dry Weight Tiller (Electric) (L) (kg)	53 (117lbs)
Dry Weight Tiller (PTT) (L) (kg)	N/A
Dry Weight RC (S) (kg)	N/A
Dry Weight RC (L) (kg)	N/A
Dry Weight RC (X) (kg)	N/A
Dry Weight Power Tilt (S) (kg)	58 (129lbs)
Dry Weight Power Tilt (L) (kg)	60 (133lbs)