

# BF25

## Engine

Type	4-Stroke OHC Twin Cylinder
Displacement (cc)	552 cc (33.7 cubic in)
Bore and Stroke (mm)	61 x 63 mm (2.4 x 2.5 in)
Full throttle RPM range (rpm)	5000-6000
HP rating at Propshaft (HP)	25HP @ 5,500 RPM
Induction Scavenging	SOHC
Valves per cylinder	2
Fuel delivery	3 Venturi
Ignition system	Programmed Ignition System
Starting system	Manual/Electric
Lubrication	Wet Sump
Cooling system	Water Cooled
Alternator (Electric)	10A (126)
Alternator (Manual)	4A (50W)
Trim Range (degrees)	5 Stage: 4°, 8°, 12°, 16°, 20°
Tilt Range (degrees)	67° / -4° - +64°

## Drive

Gear Ratio	2.08:1 (13/27)
Gear Shift	F-N-R
Propeller	3 Blade Aluminum

## Dimensions & Weight

Recommended transom height (S) (mm)	381 (15")
Recommended transom height (L) (mm)	508 (20")
Recommended transom height (X) (mm)	N/A
Recommended transom height (XX) (mm)	N/A
Dry Weight (S) (kg)	N/A
Dry Weight (L) (kg)	N/A
Dry Weight (X) (kg)	N/A
Dry Weight (XX) (kg)	N/A
Dry Weight Tiller (Manual) (S) (kg)	70 kg / 155 lbs
Dry Weight Tiller (Electric) (S) (kg)	49.5/52.5 (109/116lbs)

Dry Weight Tiller (Manual) (L) (kg)	(L) 72 kg / 160 lbs
Dry Weight Tiller (Electric) (L) (kg)	49.5/52.5 (109/116lbs)
Dry Weight Tiller (PTT) (L) (kg)	N/A
Dry Weight RC (S) (kg)	N/A
Dry Weight RC (L) (kg)	N/A
Dry Weight RC (X) (kg)	N/A
Dry Weight Power Tilt (S) (kg)	79 kg / 174 lbs
Dry Weight Power Tilt (L) (kg)	81 kg / 179 lbs