

BF5

Engine

Type	4-Stroke OHV Single Cylinder
Displacement (cc)	127 (7.8 cubic ")
Bore and Stroke (mm)	60 x 45 (2.4 x 1.8")
Full throttle RPM range (rpm)	4500-5500
HP rating at Propshaft (HP)	5@5000RPM
Induction Scavenging	OHV
Valves per cylinder	2
Fuel delivery	Single Venturi
Ignition system	Digital CDI
Starting system	Manual
Lubrication	Wet Sump
Cooling system	Water Cooled
Alternator (Electric)	Optional 3A (38W)
Alternator (Manual)	Optional 3A (38W)
Trim Range (degrees)	5 stage 5°-9°-13°-17°-21°
Tilt Range (degrees)	70°

Drive

Gear Ratio	2.08:1
Gear Shift	F-N-R
Propeller	3 Blade Polypropylene

Dimensions & Weight

Recommended transom height (S) (mm)	381 (15")
Recommended transom height (L) (mm)	508 (20")
Recommended transom height (X) (mm)	N/A
Recommended transom height (XX) (mm)	N/A
Dry Weight (S) (kg)	27 (60lbs)
Dry Weight (L) (kg)	27.5 (61lbs)
Dry Weight (X) (kg)	N/A
Dry Weight (XX) (kg)	N/A
Dry Weight Tiller (Manual) (S) (kg)	N/A
Dry Weight Tiller (Electric) (S) (kg)	N/A

Dry Weight Tiller (Manual) (L) (kg)	N/A
Dry Weight Tiller (Electric) (L) (kg)	N/A
Dry Weight Tiller (PTT) (L) (kg)	N/A
Dry Weight RC (S) (kg)	N/A
Dry Weight RC (L) (kg)	N/A
Dry Weight RC (X) (kg)	N/A
Dry Weight Power Tilt (S) (kg)	N/A
Dry Weight Power Tilt (L) (kg)	N/A