

HONDA

The Power of Dreams

Models	BFP60
ENGINE	
Engine	Manual
Type	4-Stroke Inline 3-Cylinder
Displacement (cc)	998
Bore and Stroke (mm)	73 x 79.5 (2.87 x 3.13")
Full Throttle RPM Range (rpm)	5000-6000
Rating At Prop shaft (HP)	60@5500RPM
Induction Scavenging	SOHC
Valves per cylinder	4
Fuel Delivery	Programmed Fuel Injection
Ignition System	Microcomputer Programmed
Starting System	Electric
Lubrication	Wet Sump
Cooling System	Water Cooled
Alternator (Electric)	22A
Alternator (Manual)	N/A
Trim Range (degrees)	-4º to 16º
Tilt Range (degrees)	3 Stage: 7°, 13°, 21°
DRIVE	
Drive	Manual
Gear Ratio	2.33:1
Gear Shift	F-N-R
Propeller	Optional
DIMENSIONS AND WEIGHTS	
Dimensions And Weight	Manual
Recommended Transom Height (S) (mm)	N/A
Recommended Transom Height (L) (mm)	521 (20")
Recommended Transom Height (X) (mm)	648 (25")
Recommended Transom Height (XX) (mm)	N/A
Dry Weight (S) (kg)	N/A
Dry Weight (L) (kg)	116 (255lbs)
Dry Weight (X) (kg)	122 (269lbs)
Dry Weight (XX) (kg)	N/A
Dry Weight Tiller (S) (Manual) (kg)	N/A
Dry Weight Tiller (S) (Electric) (kg)	N/A
Dry Weight Tiller (L) (Manual) (kg)	N/A
Dry Weight Tiller (L) (Electric) (kg)	N/A
Dry Weight RC (S) (kg)	N/A
Dry Weight RC (L) (kg)	N/A
Dry Weight RC (X) (kg)	N/A
Dry Weight Power Tilt (S) (kg)	N/A
Dry Weight Power Tilt (L) (kg)	N/A

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.