



Models	CRF450R CRF450R
GENERAL	
Warranty	None
Service Intervals	As per owners manual
0 - 100 km/h (sec)	-
DIMENSIONS AND WEIGHTS	
Claimed KERB Weight	105.8
Length (mm)	2182
Width (mm)	827
Height (mm)	1267
Seat height (mm)	965
Rake/Trail (°/mm)	114
Wheel Base	1481
DRIVE	
Drive	Chain
Front Suspension	Showa 49mm USD fork
Rear Suspension	Showa monoshock using Honda ProLink
ENGINE	
Tank Capacity (l)	6.3
Starter	SelfStarter
Engine Configuration	Liquidcooled 4stroke single cylinder unicam
Cylinders	1
Valves per Cylinder	4
Capacity	449.7cc
Power (KW)	-
Torque (NM)	-
Gearbox	5-spd
SAFETY	
Brakes	(f) Single 260mm disk and (r) Single 240mm disk
STYLING	
Frame Material	Aluminium twin tube
WHEELS	
Tyres Front	80/1002151M Dunlop MX33F
Tyres Rear	120/801963M Dunlop MX33
Wheels	Aluminium spoke
STANDARD AVAILABLE ACCESSORIES	
Luggage	-
Maintenance	-
Comfort	-
Utility	-

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.