

Service Internals	Models	CB750 Hornet CB750 Hornet
Service Intervals 1,2000 km 1,2000 k	GENERAL	CB730 Homes
Service Intervals 1,2000 km 0 - 100 km/n (seet)	Warranty	2 yrs
DIMENSIONS AND WEIGHTS 190	Service Intervals	
DIMENSIONS AND WEIGHTS 190	0 - 100 km/h (sec)	_
Claimed KERB Weight 190 2000		
Length (mm) 2090 Width (mm) 780 Height (mm) 1085 Seak Height (mm) 99 Wheel Base 1420 DRIVE Chain Front Suspension Showa 41mm SFF-BPTM USD. 130 mm travel. Rear Suspension Monoshock damper. Pro-Link swingarm. 150 mm travel. ENGINE 15.2 Starter Blectric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valves per Cylinder 4 Valves per Cylinder Capacity 755cc Power (KW) 67,35kW J 9,500pm Torque (NM) 758m @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY ABS Type: 2 channel. Front. Dual 296 mm x 4 mm disc with single piston calipers. STYLING Frome Material Steel diamond WHEELS Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AWALABLE ACCESSORIES Luggase - Luggase - Kaintenance -		190
Width (mm) 780 Height (mm) 1085 Seat height (mm) 99 Wheel Base 1420 DRIVE Chain Pork Chain Font Suspension Showa 41mm SFF-BPTM USD, 130 mm travel. Rear Suspension Monoshock damper, Pro-Link wingarm, 150 mm travel. ENGINE 15.2 Starter Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valvies per Cylinder 4 Valvies per Cylinder Capacity 7.55 cc Power (KW) 6.75 kW / 9.000pm Torque (NM) 7.55 kW / 9.000pm Torque (NM) 7.55 kW / 9.000pm Gearbox 6.5 speed Manual Transmission SAFETY Strate Dual 206 mm x 4 mm disc with Nissin radial mount 4-piston calipers, Rear Single 240 mm x 5 mm disc with single piston calipers. STYLING 120.702/R-17 Tyres Front 120.702/R-17 Tyres Rear 10.0602/R-17 Wheels Wheels Front: 5%-Spoke Cast Alumininum Wheels Rear: 5%-Spoke Cast Alumininum		
Height (mm)		
Seat height (mm) 795 Rakefrail (frmm) 99 Wheel Base 1420 Drive Chain Front Suspension Showa 41mm SFF-BPTM USD. 130 mm travel. Rear Suspension Monoshock damper, Pro-Link swingarm. 150 mm travel. Rear Suspension Monoshock damper, Pro-Link swingarm. 150 mm travel. Rear Suspension Monoshock damper, Pro-Link swingarm. 150 mm travel. ENGINE ENGINE Engine Confliguration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 2 Valves per Cylinder 4 Valves per Cylinder Capacity 755cc Power (RW) 755mm 97.250rpm Gearbox 6 speed Manual Transmission SAFETY ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rears: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frome Material Steed diamond WHEELS Tyres Front 120/702R-17 Tyres Rear 106/602R-17 Wheels Wheels Front: SY-Spoke Cast Aluminium Wheels Rear: SY-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage . Maintenance . Comfort 5-inch Full Colour TFT Display		
Rake/Trail (*/mm) 99 Wheel Base 1420 DRIVE Drive Chain Front Suspension Shows 41mm SFF.8PTM USD. 130 mm travel. Rear Suspension Monoshock damper, Pro-Link swingarm. 150 mm travel. ENGINE Tank Capacity (I) 15.2 Silarter Electric Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valves per Cylinder 4 Valves per Cylinder Capacity 755cc Power (KW) 755kW / 9,500rpm Torque (NM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY Brakes ABS Type: 2 channel, Front: Dual 286 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: SY-Spoke Cast Aluminium Wheels Rear; 5Y-Spoke Cast Aluminium STNDARD AVAILABLE ACCESSORIES Luggage . Maintenance . Comfort S-inch Full Colour TFT Display		
Wheel Base 1420 DRIVE Drive Chain Front Suspension Showa 41mm SFT-BPTM USD. 130 mm travel. Rear Suspension Monoshock damper, Pro-Link swingarm. 150 mm travel. BegilNE Tank Capacity (1) 15.2 Starter Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valves per Cylinder 4 Valves per Cylinder Capacity 7755cc Power (KW) 67.5km / 9.500rpm Tarque (NM) 75Nm @ 7.250rpm Gearbox 6 speed Manual Transmission SAFETY BASS Type: 2 channel, Front: Dual 296 mm x 4 mm disc with hissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single strong and surface of the single strong and surface in the single		
DRIVE Chain Front Suspension Showa 41mm SFF-BPTM USD. 130 mm travel. Rear Suspension Monoshock damper, Pro-Unk swingarm. 150 mm travel. ENGINE Tank Capacity (f) Starter Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-com Cylinders 2 Valves per Cylinder 4 Valves per Cylinder Capacity 755cc Power (KW) 67.5kW /9.500rpm Torque (NM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston calipers. STYLING Trame Material Steel diamond WHEELS Tyres Front 120/702R-17 Tyres Rear 160/602R-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Comfort 5-inch Full Colour TFT Display		
Front Suspension Showa 41mm SFF-BPTM USD. 130 mm travel. Rear Suspension Monoshock damper, Pro-Link swingarm. 150 mm travel. ENGINE Tank Capacity (I) 15.2 Starter Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valves per Cylinder 4 Valves per Cylinder Capacity 7755cc Power (KW) 755cc Power (KW) 67.5kW / 9,500rpm Torque (MM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear-Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage - Maintenance - Comfort 5-inch Full Colour TFT Display	DRIVE	
Front Suspension Showa 41mm SFF-BPTM USD. 130 mm travel. Rear Suspension Monoshock damper, Pro-Link swingarm. 150 mm travel. ENGINE Tank Capacity (I) 15.2 Starter Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valves per Cylinder 4 Valves per Cylinder Capacity 7755cc Power (KW) 755cc Power (KW) 67.5kW / 9,500rpm Torque (MM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear-Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage - Maintenance - Comfort 5-inch Full Colour TFT Display	Drive	Chain
Rear Suspension Monoshock damper, Pro-Link swingarm. 150 mm travel. ENGINE Tank Capacity (I) 15.2 Starter Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valves per Cylinder 4 Valves per Cylinder Capacity 755cc Power (KW) 67.5kW / 9.500rpm Torque (NM) 75Nm @ 7.250rpm Gearbox 6 speed Manual Transmission SAFETY Brakes ABS Type: 2 channel, Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-plston calipers. Rear: Single 240 mm x 5 mm disc with Nissin radial mount 4-plston calipers. Rear: Single 240 mm x 5 mm disc with Nissin radial mount 4-plston calipers. Rear: Single 240 mm x 5 mm disc with Nissin radial mount 4-plston calipers. Rear: Single 240 mm x 5 mm disc with Nissin radial mount 4-plston calipers. Rear: Single 240 mm x 5 mm disc with Single STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Vheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: SY-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage Maintenance Comfort 5-inch Full Colour TFT Display		
ENGINE Tank Capacity (I) Starter Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valves per Cylinder 4 Valves per Cylinder Capacity 755cc Power (KW) 67.5kW / 9,500rpm Torque (NM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY Brakes ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: SY-Spoke Cast Aluminium Wheels Rear: SY-Spoke Cast Aluminium Wheels Rear: SY-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage Maintenance 6 S-inch Full Colour TFT Display		
Tank Capacity (I) Starter Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valves per Cylinder A Valves per Cylinder Capacity 755cc Power (KW) 67.5kW / 9,500rpm Torque (NM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY ### ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING STYLING #### ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING #### ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING #### ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING #### ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING #### ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with Nissin radial mount 4-piston calipers. ##### ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. ##### ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. ###################################		The state of the s
Electric Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam Cylinders 2 Valves per Cylinder A Valves per Cylinder Capacity 755cc Power (KW) 67.5kW / 9.500rpm Torque (NM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rean: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rean: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage Maintenance Comfort S-inch Full Colour TFT Display		15.2
Engine Configuration Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-came of the parallel Twin with 270° crank and uni-came		
Cylinders 2 Valves per Cylinder 4 Valves per Cylinder Capacity 755cc Power (KW) 67.5kW / 9,500rpm Torque (NM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: SY-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage - C Maintenance - C Comfort 5-inch Full Colour TFT Display		
Valves per Cylinder Capacity 7755cc Power (KW) 67.5kW / 9,500rpm Torque (NM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston calipers. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage - C Maintenance - C Comfort 5-inch Full Colour TFT Display		
Capacity 755cc Power (KW) 67.5kW / 9,500rpm Torque (NM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS 120/702R-17 Tyres Front 120/702R-17 Tyres Rear 160/602R-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: SY-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage - Maintenance 5-inch Full Colour TFT Display		
Power (KW) 67.5kW / 9,500rpm Torque (NM) 75Nm @ 7,250rpm Gearbox 6 speed Manual Transmission SAFETY Brakes ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Pront: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage - C Maintenance - S-inch Full Colour TFT Display		
Gearbox 6 speed Manual Transmission SAFETY Brakes ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Alum	Power (KW)	67.5kW / 9,500rpm
ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage - C Maintenance - S-inch Full Colour TFT Display	Torque (NM)	75Nm @ 7,250rpm
ABS Type: 2 channel. Front: Dual 296 mm x 4 mm disc with Nissin radial mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage Maintenance Comfort 5-inch Full Colour TFT Display	Gearbox	6 speed Manual Transmission
Brakes mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single piston caliper. STYLING Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage - C Maintenance - Comfort 5-inch Full Colour TFT Display	SAFETY	
Frame Material Steel diamond WHEELS Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Alum	Brakes	mount 4-piston calipers. Rear: Single 240 mm x 5 mm disc with single
Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage	STYLING	
Tyres Front 120/70ZR-17 Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage Maintenance Comfort 5-inch Full Colour TFT Display	Frame Material	Steel diamond
Tyres Rear 160/60ZR-17 Wheels Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage	WHEELS	·
Wheels Front: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium Wheels Rear: 5Y-Spoke Cast Aluminium STANDARD AVAILABLE ACCESSORIES Luggage - Maintenance - Comfort 5-inch Full Colour TFT Display	Tyres Front	120/70ZR-17
STANDARD AVAILABLE ACCESSORIES Luggage - Maintenance - Comfort 5-inch Full Colour TFT Display	Tyres Rear	160/60ZR-17
Luggage Maintenance	Wheels	
Maintenance - Comfort 5-inch Full Colour TFT Display	STANDARD AVAILABLE ACCESSORIES	
Maintenance - Comfort 5-inch Full Colour TFT Display	Luggage	-
	Maintenance	-
	Comfort	5-inch Full Colour TFT Display
ouncy I Diudlouti	Utility	Bluetooth

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.