

	Models	GLH1800
Service Intervals   12000 km	GENERAL	GLH1800 DC1
5ervice Intervals         1.2000 km           0 - 100 km/s (seef)         -           DAMENSIONS AND WITGHTS         -           Claimed KERB Weight         Gold Wing; DCT 364kg Gold Wing Tour'; DCT with Air Bag 383kg           Length (mm)         2615           Width (mm)         905           Height (mm)         14320           Seet height (mm)         109           Wheel Base         1693           DBVE         1698           DBVE         Pro Link           Forth Superadion         Doubtle withhone           Rear Suspension         Pro Link           ROSINE         Pro Link           Starter         Intergraded Starter Generator System           Engine Configuration         Liquid-cooled 4-stroke 24 valve SOHC flat-6           Cylinders         6           Valves per Cylinder         4           Capacity         333W55500rpm           Torque (With)         334W55500rpm           Torque (With)         334W55500rpm           Torque (With)         334W55500rpm           Torque (With)         1704m45500rpm           Gearbox         7-spd           SFFETY         Interpractice Combined ABS system. (f) 320mm 4.5mm dual hybrail cylinder Combined ABS system.) (		2 vrs
DIMENSIONS AND WEIGHTS		
DIMENSIONS AND WEIGHTS		12000 KIII
Claimed KERB weight         Gold Wing: DCT 364kg Gold Wing 'flour': DCT with Air Bag 383kg           Length (mm)         2615           Width (mm)         905           Height (mm)         1 430           Seat height (mm)         745           Rakerfall (*/mm)         109           Wheel Buse         1095           DRIVE           Drive         Enclosed shaft           Front Suspension         Pro Link           Rear Suspension         Pro Link           Tank Capacity (f)         21.1           Starter         Intergroted Starter Generator System           Engine Configuration         Liquid-cooled 4-stroke 24 valve SOHC flat-6           Cylinders         6         Valves per Cylinder           Capacity         4         4         Capacity         4         Capacity         4         Capacity         9 3kW/s500rgm         Control         Control <t< td=""><td></td><td>-</td></t<>		-
Length (mm)         2615           Width (mm)         905           Height (mm)         1430           Seat height (mm)         745           Rake/Trail (*mm)         109           Wheel Base         1095           DRIVE           Drive         Enclosed shaft           Front Suspension         Pro Link           Enclosed shaft           Front Suspension         Pro Link           Enclosed shaft           Front Capacity (I)           Starter           Intergrated Starter Generator System           Englise Configuration         Liquid-cooled 4-stroke 24 valve SOHC flat-6           Cylinders         6           Cylinders         4           Capacity         1833           Power (NM)         938W/S500rpm           Costroko         7-Spd           SAFETY           Electronically-controlled combined ABS system. (f) 320mm 4.5mm dual hydrafull cids with 6-pist controlled and pads. (f) 315 mm x 12mm ventilated disc with 6-pist controlled and pads. (f) 315 mm x 12mm ventilated disc with 6-pist control and sintered metal pads. (f) 315 mm x 12mm ventilated disc with 6-pist control control centrol recolspan="2">Control Centrol Cent	i i	
Width (rmm)         905           Height (rmm)         1430           Seat height (rmm)         109           Wineel Base         1695           DRIVE         Enclosed shaft           Front, Suspension         Double wishbore           Rear Suspension         Pro Link           ENGINE         Pro Link           ENGINE         The Capacity (f)           Starter         Intergrated Starter Generator System           Engine Configuration         Liquid-cooled 4-stroke 24 valve SOHC flat-6           Cylinders         6           Valves per Cylinder         4           Capacity         1833           Power (KW)         93KW/5500pm           Torque (NM)         170Nnv4500rpm           Gearbox         7-spd           SAFETY         STUING           Frame Material         Aluminium Die Cast, Twin Tube           WHEELS         Tyres Front           Tyres Rear         200558 16           Wheels         13070 R18           Tyres Rear         1010w-section 5-spoke cast aluminium           STANDARD AVAILABLE ACCESSORIES         SRS CS Auto 6-speaker 80W surround-sounds system with USB Electron I windsheld Smart Rey (Reyleas start) Control Center           Maintenance		
Height (mm)		
Seat helight (mm) 745 Rake/Trail (f/mm) 109 Wheel Base 1055 Drive 61655 Drive 7500 1000 wishbone 100		
Rake/Irail (*/mm) Wheel Base 1695  DRIVE  Drive Enclosed shaft Front Suspension Roar Suspensio	Height (mm)	1430
Wheel Base         1695           DRIVE           Drive         Enclosed shaft           Front Suspension         Double wishbone           Rear Suspension         Pro Link           ENGINE           Tank Capacity (f)           Starter           Engine Configuration         Liquid-cooled 4-stroke 24 valve 50HC flat-6           Cylinders         6           Valves per Cylinder         4           Capacity         1893           Power (KW)         938W/950rpm           Torque (NM)         170Nm/450orpm           Gearbox         7-spd           SAFETY           Brakes         Electronically-controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 1mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 1mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 1mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 1mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 1mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 1mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 1mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 1mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 1mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 1mm venti	Seat height (mm)	745
DRIVE  Drive Enclosed shaft Front Suspension Double wishbone Rear Suspension Pro Link  ENGINE  ENGINE  Tank Capacity (I) 21.1  Starter Intergrated Starter Generator System Engine Configuration Liquid-cooled 4-stroke 24 valve SOHC flat-6  Cylinders 6  Valves per Cylinder 4  Capacity 1333  Power (KW) 93kKW/5500rpm  Torque (NM) 170N/N/4500rpm  Gearbox 7-spd  SAFETY   Electronically controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 317 mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (f) 316mm x	Rake/Trail (°/mm)	109
Drive         Enclosed shaft           Front Suspension         Double wishbone           Rear Suspension         Pro Link           ENGINE         Tank Capacity (I)           Starter         Intergrated Starter Generator System           Engine Confliguration         Liquid-cooled 4-stroke 24 valve SOHC flat-6           Cylinders         6           Valves per Cylinder         4           Capacity         1833           Power (KW)         93kW/5500rpm           Torque (NM)         170km/4500rpm           SAFETY         SAFETY           STYLING         Electronically-controlled combined ABS system, (I) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads, (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads.           STYLING         Time Material           WHEELS         Aluminium Die Cast, Twin Tube           WHEELS         Tyres Front           Tyres Rear         200/55R 16           Wheels         Hollow-section 5-spoke cast aluminium           STADDARD AVAILABLE ACCESSORIES         SRS CS Auto 6-speaker 80W surround-sounds system with USB Electronic windshield Smart Key (Keyless start) Control Center           Maintenance         Apple Car Play Navigation           Gomfort         Bluetooth Connectivity 7-inch full colour, TFT liquid cry	Wheel Base	1695
Front Suspension Double wishbone Rear Suspension Pro Link  ENGINE  Tank Capacity (I) 2.1.1  Starter Intergrated Starter Generator System Engine Configuration Liquid-cooled 4-stroke 24 valve SOHC flat-6 Cylinders 6 Valves per Cylinder 4 Capacity 1833 Power (KW) 93kW/5500rpm Torque (NM) 170Nrv/4500rpm Gearbox 7-spd  SAFETY  Bleetronically-controlled combined ABS system. (I) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r ) 315mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads  STYLING  Frame Material Aluminium Die Cast, Twin Tube  WHEELS  Tyres Front 130,70 R18 Tyres Rear 200,55R 16 Wheels Hollow-section 5-spoke cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage SRS S Auto 6-speaker 80W surround-sounds system with USB Electronic Maintenance Apple Car Play Navigation  Engine Composition of the Colonic	DRIVE	
Rear Suspension Pro Link  ENGINE  Tank Capacity (1) 21.1  Starter Intergrated Starter Generator System Engine Configuration Liquid-cooled 4-stroke 24 valve SOHC flat-6  Cylinders 6  Valves per Cylinder 4  Capacity 333  Power (KW) 393kW/S500rpm  Torque (NM) 170Nm/4500rpm  Torque (NM) 27-spd  SAFETY  Brakes Electronically-controlled combined ABS system. (1) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered m	Drive	Enclosed shaft
Engine Capacity (I) 2.1.1  Starter Intergrated Starter Generator System Engine Configuration Liquid-cooled 4-stroke 24 valve SOHC flat-6 Cylinders 6 Valves per Cylinder 4 Capacity 1833 Power (KW) 1833 Power (KW) 93kW;5500rpm Torque (NM) 170Nm/4500rpm Gearbox 7-spd  SAFETY  Brakes Electronically-controlled combined ABS system. (I) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads.  STYLING  Frame Material Aluminium Die Cast, Twin Tube  WHEELS  Tyres Front 130/70 R18 Tyres Rear 200/55R 16 Wheels 150/50 SA LOCAS SORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electronic Maintenance Apple Car Play Navigation Comfort Bluetoth Connectivity 7-inch full colour, TFT liquid crystal screen Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Front Suspension	Double wishbone
Tank Capacity (I)  Starter  Intergrated Starter Generator System Engine Configuration  Engine Configuration  Eliquid-cooled 4-stroke 24 valve SOHC flat-6  Cylinders  Generator System  6  Valves per Cylinder  Capacity  Engine (KW)  Capacity  Engine (KW)  Engine (KW)	Rear Suspension	Pro Link
Starter Intergrated Starter Generator System Engine Configuration Liquid-cooled 4-stroke 24 valve SOHC flat-6 Cylinders 6 Valves per Cylinder 4 Capacity 1833 Power (KW) 93kW/5500rpm Torque (NM) 93kW/5500rpm Torque (NM) 170Nm/4500rpm Gearbox 7-spd SAFETY  Brakes Electronically-controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads.  STYLING  Frame Material Aluminium Die Cast, Twin Tube  WHEELS  Tyres Rear 200/55R 16 Wheels 130/70 R18 Tyres Rear 200/55R 16 Wheels Hollow-section 5-spoke cast aluminium STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electronic Maintenance Apple Car Play Navigation Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	ENGINE	
Engine Configuration  Cylinders 6 Valves per Cylinder 4 Capacity 1833 Power (KW) 93kW/5500rpm Torque (NM) 6earbox 7-spd  SAFETY  Electronically-controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. (r) 316mm x 15TYLING  Frame Material MHEELS Tyres Front 130/70 R18 Tyres Rear 200/55R 16 Wheels Hollow-section 5-spoke cast aluminium STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electronic windshield Smart Key (Keyless start) Control Center Maintenance Apple Car Play Navigation Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Tank Capacity (I)	21.1
Cylinders 6 Valves per Cylinder 4 Capacity 1833 Power (KW) 93kW/5500rpm Torque (NM) 170Nm/4500rpm Gearbox 7-spd  SAFETY  Brakes Electronically-controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads. SYLING  Frame Material Aluminium Die Cast, Twin Tube  WHEELS Tyres Front 130/70 R18 Tyres Rear 200/55R 16 Wheels 130/70 R18  Tyres Rear 200/55R 16 Wheels Aluminium Die Cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance Apple Car Play Navigation  Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Starter	Intergrated Starter Generator System
Valves per Cylinder Capacity 1833 Power (KW) 93kW/5500rpm Torque (NM) 170Nm/4500rpm Gearbox 7-spd SAFETY  Brakes Brakes Brakes Blectronically-controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads.  STYLING Frame Material MAterial MAterial MAterial MHEELS Tyres Front 130/70 R18 Tyres Rear 200/55R 16 Wheels Hollow-section 5-spoke cast aluminium STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center Maintenance Apple Car Play Navigation Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Engine Configuration	Liquid-cooled 4-stroke 24 valve SOHC flat-6
Capacity     1833       Power (KW)     93kW/5500rpm       Torque (NM)     170Nm/4500rpm       Gearbox     7-spd       SAFETY     Electronically-controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads.       STYLING     Aluminium Die Cast, Twin Tube       WHEELS     130/70 R18       Tyres Front     130/70 R18       Tyres Rear     200/55R 16       Wheels     Hollow-section 5-spoke cast aluminium       STANDARD AVAILABLE ACCESSORIES     SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center       Maintenance     Apple Car Play Navigation       Comfort     Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Cylinders	6
Power (KW) 93kW/5500rpm  Torque (NM) 170Nm/4500rpm  Gearbox 7-spd  SAFETY  Brakes Electronically-controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads.  STYLING  Frame Material Aluminium Die Cast, Twin Tube  WHEELS  Tyres Front 130/70 R18  Tyres Rear 200/55R 16  Wheels Hollow-section 5-spoke cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance Apple Car Play Navigation  Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Valves per Cylinder	4
Torque (NM) Gearbox FAFETY  Brakes Br	Capacity	1833
Gearbox SAFETY  Brakes	Power (KW)	93kW/5500rpm
Electronically-controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads.  STYLING  Frame Material Aluminium Die Cast, Twin Tube  WHEELS  Tyres Front 130/70 R18  Tyres Rear 200/55R 16  Wheels BHollow-section 5-spoke cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance Apple Car Play Navigation  Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Torque (NM)	170Nm/4500rpm
Brakes Electronically-controlled combined ABS system. (f) 320mmx 4.5mm dual hydraulic disc with 6-piston rotors and sintered metal pads. (r ) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads.  STYLING  Frame Material Aluminium Die Cast, Twin Tube  WHEELS  Tyres Front 130/70 R18  Tyres Rear 200/55R 16  Wheels Hollow-section 5-spoke cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance Apple Car Play Navigation  Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Gearbox	7-spd
Brakes hydraulic disc with 6-piston rotors and sintered metal pads. (r ) 316mm x 11mm ventilated disc with 3-piston calliper and sintered metal pads.  STYLING  Frame Material Aluminium Die Cast, Twin Tube  WHEELS  Tyres Front 130/70 R18  Tyres Rear 200/55R 16  Wheels Hollow-section 5-spoke cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance Apple Car Play Navigation  Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	SAFETY	
Frame Material Aluminium Die Cast, Twin Tube  WHEELS  Tyres Front 130/70 R18  Tyres Rear 200/55R 16  Wheels Hollow-section 5-spoke cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance Apple Car Play Navigation  Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Brakes	hydraulic disc with 6-piston rotors and sintered metal pads. (r ) 316mm x
WHEELS Tyres Front 130/70 R18 Tyres Rear 200/55R 16 Wheels Hollow-section 5-spoke cast aluminium STANDARD AVAILABLE ACCESSORIES Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center Maintenance Apple Car Play Navigation Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	STYLING	
Tyres Front 130/70 R18  Tyres Rear 200/55R 16  Wheels Hollow-section 5-spoke cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance Apple Car Play Navigation  Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Frame Material	Aluminium Die Cast, Twin Tube
Tyres Rear  200/55R 16  Wheels  Hollow-section 5-spoke cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage  SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance  Apple Car Play Navigation  Comfort  Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	WHEELS	
Wheels Hollow-section 5-spoke cast aluminium  STANDARD AVAILABLE ACCESSORIES  Luggage SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance Apple Car Play Navigation  Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Tyres Front	130/70 R18
STANDARD AVAILABLE ACCESSORIES  Luggage  SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Maintenance  Apple Car Play Navigation  Comfort  Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Tyres Rear	200/55R 16
Luggage  SRS CS Auto 6-speaker 80W surround-sounds system with USB Electroni windshield Smart Key (Keyless start) Control Center  Apple Car Play Navigation  Comfort  Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Wheels	Hollow-section 5-spoke cast aluminium
Windshield Smart Key (Keyless start) Control Center         Maintenance       Apple Car Play Navigation         Comfort       Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	STANDARD AVAILABLE ACCESSORIES	
Comfort Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen	Luggage	
	Maintenance	Apple Car Play Navigation
	Comfort	Bluetooth Connectivity 7-inch full colour, TFT liquid crystal screen
Utility Heated Grips, seat including Pillion seat Air bag	Utility	Heated Grips, seat including Pillion seat Air bag

## **DISCLAIMER**

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.