

Models	GX390
ENGINE	
Туре	Air cooled 4-stroke OHV petrol engine
Bore and Stroke (mm)	88 x 64
Displacement (cc)	389
Compression Ratio	8.2:1
Ignition System	CDI
Starting System	Recoil; Electric/Recoil
ACG Output	N/A
Oil Capacity (I)	1,1
Fuel Tank Capacity (I)	6,1
Air Cleaner	Semi-dry; Oil bath; Dual; Silent; Cyclone
Fuel Consumption At Rated Power	3.5 L/h
DATA	
Net Power @ 3 600rpm (kW) (in accordance with SAEJ1349)	8.7 (11.6)
Net Torque @ 2 500rpm (Nm) (in accordance with SAEJ1349)	26,5
Dimensions and Weight	
Dimensions (L x W x H) (mm)	380 × 450 × 443
Dry Weight (kg)	31,5

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.