

| Models | EU22i |
|------------------------------------|---|
| DRIVE | |
| AC Frequency (hz) | 50 |
| AC Output Voltage (V) | 220 |
| Rated AC Output (kVA) | 1,8 |
| Max AC Output (kVa) | 2,2 |
| DC Output | 12V-8A |
| Continuous Operating Hours (hrs) | 3.3 hrs |
| Operating Noise Level @ 7m (dB(A)) | LwA 91db(A)** |
| ENGINE | _ |
| Model | GXR120 |
| Туре | Forced air-cooled, 4 stroke, OHV, single cylinder |
| Displacement (cc) | 121 |
| Ignition System | Fully Transistorized |
| Starting System | Recoil |
| Fuel Tank Capacity (I) | 3,6 |
| DIMENSIONS AND WEIGHT | |
| Dimensions (L x W x H) (mm) | 511 x 290 x 425 |
| Dry weight (kg) | 21 |
| FEATURES | |
| Eco Throttle | Yes |
| Oil Alert | Yes |
| Fuel Gauge | No |
| Capacity Air Cleaner | Yes |
| Large Capacity Muffler | Yes |
| Accessory AC Plug | Yes |
| Automatic Voltage Regulator | No |
| Voltmeter | No |
| AC Circuit Breaker | Yes |
| DC Circuit Breaker | Yes |
| 2/4-Wheel Dolly Kit | N/A |
| Electric Starter | No |
| Battery Tray Kit | No |
| Pilot Lamp | N/A |
| Receptacle 1 | type B plug included |
| Receptacle 2 | type B plug included |
| Receptacle 3 | N/A |

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.